

Алматы (7273)495-231	Ижевск (3412)26-03-58	Магнитогорск (3519)55-03-13	Пермь (342)205-81-47	Тверь (4822)63-31-35
Ангарск (3955)60-70-56	Иваново (4932)77-34-06	Москва (495)268-04-70	Ростов-на-Дону (863)308-18-15	Тольятти (8482)63-91-07
Архангельск (8182)63-90-72	Иркутск (395)279-98-46	Мурманск (8152)59-64-93	Рязань (4912)46-61-64	Томск (3822)98-41-53
Астрахань (8512)99-46-04	Казань (843)206-01-48	Набережные Челны (8552)20-53-41	Самара (846)206-03-16	Тула (4872)33-79-87
Барнаул (3852)73-04-60	Калининград (4012)72-03-81	Нижний Новгород (831)429-08-12	Саранск (8342)22-96-24	Тюмень (3452)66-21-18
Белгород (4722)40-23-64	Калуга (4842)92-23-67	Новокузнецк (3843)20-46-81	Санкт-Петербург (812)309-46-40	Улан-Удэ (3012)59-97-51
Благовещенск (4162)22-76-07	Кемерово (3842)65-04-62	Ноябрьск (3496)41-32-12	Саратов (845)249-38-78	Ульяновск (8422)24-23-59
Брянск (4832)59-03-52	Киров (8332)68-02-04	Новосибирск (383)227-86-73	Севастополь (8692)22-31-93	Уфа (347)229-48-12
Владивосток (423)249-28-31	Коломна (4966)23-41-49	Ноябрьск (3496)41-32-12	Симферополь (3652)67-13-56	Хабаровск (4212)92-98-04
Владикавказ (8672)28-90-48	Кострома (4942)77-07-48	Омск (3812)21-46-40	Смоленск (4812)29-41-54	Чебоксары (8352)28-53-07
Владимир (4922) 49-43-18	Краснодар (861)203-40-90	Орел (4862)44-53-42	Сочи (862)225-72-31	Челябинск (351)202-03-61
Волгоград (844)278-03-48	Красноярск (391)204-63-61	Оренбург (3532)37-68-04	Ставрополь (8652)20-65-13	Череповец (8202)49-02-64
Вологда (8172)26-41-59	Курск (4712)77-13-04	Пенза (8412)22-31-16	Сыктывкар (8212)25-95-17	Чита (3022)38-34-83
Воронеж (473)204-51-73	Курган (3522)50-90-47	Петрозаводск (8142)55-98-37	Сургут (3462)77-98-35	Якутск (4112)23-90-97
Екатеринбург (343)384-55-89	Липецк (4742)52-20-81	Псков (8112)59-10-37	Тамбов (4752)50-40-97	Ярославль (4852)69-52-93
Киргизия (996)312-96-26-47	Россия (495)268-04-70	Казахстан (772)734-952-31		

https://forcar.nt-rt.ru || fco@nt-rt.ru

Морозильная камера G-BD350

DEEP-FREEZERS G-BD350

SKU: G-BD350



ADDITIONAL INFORMATION

WORKING TEMPERATURE/OPERATING TEMPERATURE	≤-18
EXTERNAL DIMENSIONS	
INTERNAL DIMENSIONS	
CAPACITY	
MAX. OPERATING TEMPERATURE	+38°C/ 60%HR
TYPE OF COOLING	static
DEFROSTING TYPE	manual
TYPE OF COOLING GAS	R600a
CONDENSED WATER EVAPORATION	with drain pipe
TEMPERATURE CONTROL	mechanical
INSULATION (mm)	70
POWER CONSUMPTION (W)	
VOLTAGE	230V / 50Hz
CONSTRUCTION MATERIAL	white painted metal sheet + embossed aluminium
DOOR REVERSING	counterbalanced lid
INTERIOR LIGHT	no
SUPPLIED ACCESSORIES	defrost shovel
ENERGY CLASS	F
NET WEIGHT (Kg)	52
GROSS WEIGHT (Kg)	
PACKAGING DIMENSIONS	1080 x 780 x 890(h) mm